

A surfacer (or surface planer) is used to achieve flat and smooth surfaces on timber boards.



## FEATURES

- Spiral insert knife cutterhead with 30x12x1.5mm two sided knives.
- Spiral insert knife head runs quieter than a conventional straight knife head and provides a longer life of the cutting tools.
- Noise reduction table lips on infeed and outfeed tables for quiet operation.
- Accurate parallelogram design enables table to travel in the same arc as the cutting circle, maintaining close uniform clearance between the table lip and cutterhead for safest operation regardless of cutting depth.
- Table raising and lowering by convenient lever with locking knob to prevent accidental table movement.
- Large centre mounted fence with quick setting stops at 45°, 90° & 135°.
- Smooth fence adjustment by rack & pinion.
- Large diameter cutterhead is ground and balanced.
- Spring loaded adjusting safety guard moves only when workpiece is being fed.

## SPECIFICATIONS

Table Size	304mm x 2133mm
Max. Cutting Depth	19mm
Main Motor	5HP with Electric Brake
Cutterhead	Spiral with Replaceable Knives (30mm x 12mm x 1.5mm)
CE Approved	

A surfacer (or surface planer) is used to achieve flat and smooth surfaces on timber boards.



## FEATURES

- Spiral insert knife cutterhead with 30x12x1.5mm two sided knives.
- Spiral insert knife head runs quieter than a conventional straight knife head and provides a longer life of the cutting tools.
- Noise reduction table lips on infeed and outfeed tables for quiet operation.
- Accurate parallelogram design enables table to travel in the same arc as the cutting circle, maintaining close uniform clearance between the table lip and cutterhead for safest operation regardless of cutting depth.
- Table raising and lowering by convenient lever with locking knob to prevent accidental table movement.
- Large centre mounted fence with quick setting stops at 45°, 90° & 135°.
- Smooth fence adjustment by rack & pinion.
- Large diameter cutterhead is ground and balanced.
- Spring loaded adjusting safety guard moves only when workpiece is being fed.

## SPECIFICATIONS

Table Size	406mm x 2438mm
Max. Cutting Depth	19mm
Main Motor	7.5HP with Electric Brake
Cutterhead	Spiral with Replaceable Knives (30mm x 12mm x 1.5mm)
CE Approved	



**SP-310C**



**SP-410C**

Specifications	Surfacer	Surfacer
Table Size	304mm x 2133mm	406mm x 2438mm
Max. Cutting Depth	19mm	
Main Motor	5HP	7.5HP
Cutterhead	Spiral with Replaceable Knives (30mm x 12mm x 1.5mm)	
CE Approved	Yes	